

PRODUCT AVAILABILITY							
Collection	Pattern Name	Pattern #	Size (in)	Size (mm)	Emboss	Availability	
						Stocked	Special Order
Alleyway	Bronze Mist	DN124906ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Carbon	DN124904ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Indigo	DN124912ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Kiwi	DN124907ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Lucky Red	DN124910ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Poppy	DN124909ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Soft White	DN124901ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Stormy Grey	DN124905ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Coastal Oak	Greyed	DN821826ATX	7" x 48"	177.8mm x 1219.2mm	Saw Cut	•	
Coastal Oak	Oxidized	DN821828ATX	7" x 48"	177.8mm x 1219.2mm	Saw Cut	•	
Coastal Oak	Weathered	DN821822ATX	7" x 48"	177.8mm x 1219.2mm	Saw Cut		•
Coastal Oak	Worn Beige	DN821823ATX	7" x 48"	177.8mm x 1219.2mm	Saw Cut	•	
Oak Framing	Chalk	DN124105ATX	7" x 48"	177.8mm x 1219.2mm	Natural Timber		•
Oak Framing	Crete	DN124104ATX	7" x 48"	177.8mm x 1219.2mm	Natural Timber		•
Oak Framing	Greige	DN124114ATX	7" x 48"	177.8mm x 1219.2mm	Natural Timber		•
Oak Framing	Washed Sienna	DN124115ATX	7" x 48"	177.8mm x 1219.2mm	Natural Timber		•
Clean Oak	Fumed	DN529113ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
Clean Oak	Mist Grey	DN529107ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
Clean Oak	Natural Brown	DN529104ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
Clean Oak	Sun Bleached	DN529112ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
San Marcos Oak	Eggplant Grey	DN1445109ATX	9" x 60"	228.6mm x 1524mm	In-Register	•	
San Marcos Oak	Flint Grey	DN1445108ATX	9" x 60"	228.6mm x 1524mm	In-Register	•	
San Marcos Oak	Nordic Haze	DN1445101ATX	9" x 60"	228.6mm x 1524mm	In-Register	•	
San Marcos Oak	Pumice Washed	DN1445105ATX	9" x 60"	228.6mm x 1524mm	In-Register	•	
San Marcos Oak	Waxed Greige	DN1445117ATX	9" x 60"	228.6mm x 1524mm	In-Register	•	
San Marcos Oak	Worn Sienna	DN1445114ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
Belgium Weave	Cool Grey	DN477104ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Faded Denim	DN477105ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Limestone	DN477102ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Pearl White	DN477107ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Sand	DN477101ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Smoke	DN477103ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Smooth Concrete	Anthracite	DN123813ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete		•
Smooth Concrete	Clay	DN123809ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete	•	
Smooth Concrete	Dolomite	DN123818ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete		•
Smooth Concrete	Stoneware	DN123815ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete		•
Smooth Concrete	Umber	DN123807ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete		•
Smooth Concrete	Zinc	DN123814ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete	•	

Note - Items in **Bold Text** are those that are regularly Stocked; all other items are available via Special Order

PHYSICAL PROPERTIES & PACKAGING – PLANK				
Collections	Design	Emboss	Design	Emboss
		Alleyway Coastal Oak Oak Framing	Linen Saw Cut Natural Timber	Clean Oak San Marcus Oak
Size	7" x 48" (177.8mm x 1219.2mm)		9" x 60" (228.6mm x 1524mm)	
Construction	Solid Vinyl Tile/LVT w/Attraxion Magnetic Attachment Technology		Solid Vinyl Tile/LVT w/Attraxion Magnetic Attachment Technology	
Use	Commercial & Residential		Commercial & Residential	
Wear Layer	20 mil (0.5mm)		20 mil (0.5mm)	
Edge Detail	Micro-Bevel Edge		Micro-Bevel Edge	
Finish	FX ³ Surface Protectant with Ultra-Fresh		FX ³ Surface Protectant with Ultra-Fresh	
Gauge	Déjà New with Attraxion LVT - 2.5mm (0.098") MagneBuild Underlayment (Roll) - 1.0mm (0.039") Installed System - 3.5mm (0.138")		Déjà New with Attraxion LVT - 2.5mm (0.098") MagneBuild Underlayment (Roll) - 1.0mm (0.039") Installed System - 3.5mm (0.138")	
Pieces/Carton	16		10	
Coverage/Piece	2.33 Sq.Ft. (0.22 Sq.M.)		3.75 Sq.Ft. (0.35 Sq.M.)	
Coverage/Carton	37.33 Sq.Ft. (3.47 Sq.M.)		37.5 Sq.Ft. (3.48 Sq.M.)	
Coverage/Pallet	65 Cartons / Pallet (2,426.67 Sq.Ft. / 225.44 Sq.M.)		60 Cartons / Pallet (2,250 Sq.Ft. / 209.03 Sq.M.)	
Coverage/Container	15 Pallets / Container (36,400 Sq.Ft. / 3,381.67 Sq.M.)		16 Pallets / Container (36,000 Sq.Ft. / 3,344.51 Sq.M.)	
Limited Warranty	Commercial: 15 Years / Residential: Limited Lifetime		Commercial: 15 Years / Residential: Limited Lifetime	

PHYSICAL PROPERTIES & PACKAGING – TILE				
Collections	Design	Emboss	Design	Emboss
		Belgium Weave	Linen	Smooth Concrete
Size	16" x 32" (406.4mm x 812.8mm)		24" x 24" (609.6mm x 609.6mm)	
Construction	Solid Vinyl Tile/LVT w/Attraxion Magnetic Attachment Technology		Solid Vinyl Tile/LVT w/Attraxion Magnetic Attachment Technology	
Use	Commercial & Residential		Commercial & Residential	
Wear Layer	20 mil (0.5mm)		20 mil (0.5mm)	
Edge Detail	Square Edge		Micro-Bevel Edge	
Finish	FX ³ Surface Protectant with Ultra-Fresh		FX ³ Surface Protectant with Ultra-Fresh	
Gauge	Déjà New with Attraxion LVT - 2.5mm (0.098") MagneBuild Underlayment (Roll) - 1.0mm (0.039") Installed System - 3.5mm (0.138")		Déjà New with Attraxion LVT - 2.5mm (0.098") MagneBuild Underlayment (Roll) - 1.0mm (0.039") Installed System - 3.5mm (0.138")	
Pieces/Carton	10		9	
Coverage/Piece	3.56 Sq.Ft. (0.33 Sq.M.)		4 Sq.Ft. (0.37 Sq.M.)	
Coverage/Carton	35.56 Sq.Ft. (3.3 Sq.M.)		36 Sq.Ft. (3.34 Sq.M.)	
Coverage/Pallet	56 Cartons / Pallet (1,991.11 Sq.Ft. / 184.98 Sq.M.)		20 Cartons / Pallet (720 Sq.Ft. / 66.89 Sq.M.)	
Coverage/Container	18 Pallets / Container (35,840 Sq.Ft. / 3,329.64 Sq.M.)		50 Pallets / Container (36,000 Sq.Ft. / 3,344.51 Sq.M.)	
Limited Warranty	Commercial: 15 Years / Residential: Limited Lifetime		Commercial: 15 Years / Residential: Limited Lifetime	

PHYSICAL PROPERTIES & PACKAGING – MAGNEBUILD MAGNETIC UNDERLAYMENT	
Size	3' x 33.3' (0.914m x 10.15m)
Use	Commercial & Residential
Gauge	1.0mm (0.039")
Coverage/Roll	100 Sq.Ft. (9.29 Sq.M.)

Note – According to the manufacturer, Magnetic Building Solutions, the MagneBuild magnetic underlayment has passed the relevant fire safety tests. For the detailed information on the fire safety as well as other safety and performance tests, please go to www.magneticbuildingsolutions.com.

STANDARDS – MANUFACTURING & USAGE (ASTM F1700)

Standard	Description	Requirements	Results
ASTM F1700	Classification	Refer to Standard	Class III, Type B
ASTM F386	Thickness	Tolerance: $\pm 0.005"$ vs. Nominal	Passes Requirements
ASTM F410	Wear Layer Thickness	Commercial Classification: $\geq 0.020"$ (0.5mm)	Passes Requirements
ASTM F2421/ ASTM F2055	Size & Squareness	Size, Tolerance: $\pm 0.016"/$ Linear Foot vs. Nominal Squareness: $\leq 0.010"$	Passes Requirements
ASTM F1914	Residual Indentation	Average < 8% Maximum - Any Sample $\leq 10\%$	Surpasses Requirements ¹
ASTM F137	Flexibility	No cracks/breaks (1"/25.4mm Mandrel)	Surpasses Requirements
ASTM F2199	Dimensional Stability	$\leq 0.020"/$ Linear Foot	Surpasses Requirements
ASTM F925	Chemical Resistance	No more than "Slight Change"	Surpasses Requirements
ASTM F1514	Resistance to Heat	Average $\Delta E < 8.0$	Surpasses Requirements
ASTM F1515	Resistance to Light	Average $\Delta E < 8.0$	Surpasses Requirements

STANDARDS – SAFETY & PERFORMANCE

Standard	Description	Requirements	Results
ASTM E648	Critical Radiant Flux (Radiant Panel)	Class I: ≥ 0.45 W/Sq.Cm.	Passes Requirements ²
ASTM E662	Smoke Density	Flaming & Non-Flaming ≤ 450	Passes Requirements ³
CDPH/EHLB Standard Method v1.2	VOCs/TVOCs, Formaldehyde	Refer to Standard	Passes Requirements
REACH SVHC 191	Substances of Very High Concern	Per Substance: $\leq 0.1\%$ w/w (weight/weight)	Passes Requirements
ASTM F963	Heavy Metals	Refer to Standard	Passes Requirements
ASTM D7823 / CPSC-CH-C1001-09.3	Phthalates	Refer to Consumer Product Safety Improvement Act (CPSIA)	Passes Requirements
ASTM G21	Antifungal Activity	N/A (No Official Requirements)	Top Surface: 0 (No Growth)
ASTM D2047	Coefficient of Friction / Slip Resistance	N/A (No Official Requirements)	≥ 0.6 (Dry)
ANSI ESD STM97.2	Body Voltage	N/A (No Official Requirements)	Average (Abs): $\leq 2.0kV$ ¹
ASTM F970	Static Load	$\pm 0.005"$, 250-Lbs. Load	Passes Requirements ¹
SIM Test	Static Load Limit	Test to Limit ($\pm 0.005"$)	≥ 800 psi ¹
ASTM D4060	Abrasion Resistance	N/A (No Official Requirements)	Average: $\geq 20,000$ cycles

STANDARDS – SOUND

Product + Assembly	ASTM E90	ASTM E492	ASTM E2179	Results (Remarks)
Déjà New with Attraxion LVT Installed with MagneBuild Underlayment Over 6" Concrete Slab with Drop-Ceiling	STC 62	IIC 51	Not Applicable	Passes International Building Code requirements of STC ≥ 50 and IIC ≥ 50 for multi-story dwellings

Notes

- 1) ASTM F1914 (Residual Indentation), ANSI ESD STM97.2 (Body Voltage), ASTM F970 (Static Load), SIM Test (Static Load Limit) - results are from tests conducted on an Attraxion system (Déjà New with Attraxion LVT + MagneBuild Underlayment)
- 2) ASTM E648 - Critical Radiant Flux (Radiant Panel): Passes Requirements for Class I per International Building Code (IBC) 2018 & NFPA 101 Life Safety Code
- 3) ASTM E662 - Smoke Density: 450 is the limit established by many state, county, and/or local building and/or fire codes, but is not set as a limit for (resilient) flooring products nationwide. Thus, Smoke Density requirements for flooring products may vary from jurisdiction to jurisdiction. Consult your building inspector / fire marshal to learn more

Ultra-Fresh is a registered trademark of Thomson Research Associates, Inc.