

PRODUCT AVAILABILITY							
Collection	Pattern Name	Pattern #	Size (in)	Size (mm)	Emboss	Availability	
						Stocked	Special Order
Alleyway	Bronze Mist	DN124906ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Carbon	DN124904ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Indigo	DN124912ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Kiwi	DN124907ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Lucky Red	DN124910ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Poppy	DN124909ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Soft White	DN124901ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
Alleyway	Stormy Grey	DN124905ATX	7" x 48"	177.8mm x 1219.2mm	Linen		•
<b>Coastal Oak</b>	<b>Greyed</b>	<b>DN821826ATX</b>	<b>7" x 48"</b>	<b>177.8mm x 1219.2mm</b>	<b>Saw Cut</b>	•	
<b>Coastal Oak</b>	<b>Oxidized</b>	<b>DN821828ATX</b>	<b>7" x 48"</b>	<b>177.8mm x 1219.2mm</b>	<b>Saw Cut</b>	•	
Coastal Oak	Weathered	DN821822ATX	7" x 48"	177.8mm x 1219.2mm	Saw Cut		•
<b>Coastal Oak</b>	<b>Worn Beige</b>	<b>DN821823ATX</b>	<b>7" x 48"</b>	<b>177.8mm x 1219.2mm</b>	<b>Saw Cut</b>	•	
Oak Framing	Chalk	DN124105ATX	7" x 48"	177.8mm x 1219.2mm	Natural Timber		•
Oak Framing	Crete	DN124104ATX	7" x 48"	177.8mm x 1219.2mm	Natural Timber		•
Oak Framing	Greige	DN124114ATX	7" x 48"	177.8mm x 1219.2mm	Natural Timber		•
Oak Framing	Washed Sienna	DN124115ATX	7" x 48"	177.8mm x 1219.2mm	Natural Timber		•
Clean Oak	Fumed	DN529113ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
Clean Oak	Mist Grey	DN529107ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
Clean Oak	Natural Brown	DN529104ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
Clean Oak	Sun Bleached	DN529112ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
<b>San Marcos Oak</b>	<b>Eggplant Grey</b>	<b>DN1445109ATX</b>	<b>9" x 60"</b>	<b>228.6mm x 1524mm</b>	<b>In-Register</b>	•	
<b>San Marcos Oak</b>	<b>Flint Grey</b>	<b>DN1445108ATX</b>	<b>9" x 60"</b>	<b>228.6mm x 1524mm</b>	<b>In-Register</b>	•	
<b>San Marcos Oak</b>	<b>Nordic Haze</b>	<b>DN1445101ATX</b>	<b>9" x 60"</b>	<b>228.6mm x 1524mm</b>	<b>In-Register</b>	•	
<b>San Marcos Oak</b>	<b>Pumice Washed</b>	<b>DN1445105ATX</b>	<b>9" x 60"</b>	<b>228.6mm x 1524mm</b>	<b>In-Register</b>	•	
<b>San Marcos Oak</b>	<b>Waxed Greige</b>	<b>DN1445117ATX</b>	<b>9" x 60"</b>	<b>228.6mm x 1524mm</b>	<b>In-Register</b>	•	
San Marcos Oak	Worn Sienna	DN1445114ATX	9" x 60"	228.6mm x 1524mm	In-Register		•
Belgium Weave	Cool Grey	DN477104ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Faded Denim	DN477105ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Limestone	DN477102ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Pearl White	DN477107ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Sand	DN477101ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Belgium Weave	Smoke	DN477103ATX	16" x 32"	406.4mm x 812.8mm	Linen		•
Smooth Concrete	Anthracite	DN123813ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete		•
<b>Smooth Concrete</b>	<b>Clay</b>	<b>DN123809ATX</b>	<b>24" x 24"</b>	<b>609.6mm x 609.6mm</b>	<b>Rough Concrete</b>	•	
Smooth Concrete	Dolomite	DN123818ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete		•
Smooth Concrete	Stoneware	DN123815ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete		•
Smooth Concrete	Umber	DN123807ATX	24" x 24"	609.6mm x 609.6mm	Rough Concrete		•
<b>Smooth Concrete</b>	<b>Zinc</b>	<b>DN123814ATX</b>	<b>24" x 24"</b>	<b>609.6mm x 609.6mm</b>	<b>Rough Concrete</b>	•	

Note - Items in **Bold Text** are those that are regularly Stocked; all other items are available via Special Order

<b>PHYSICAL PROPERTIES &amp; PACKAGING – PLANK (FLOATING - 2.5MM GAUGE / 0.5MM WEAR LAYER)</b>				
<b>Collections</b>	<b>Design</b> Alleyway Coastal Oak Oak Framing	<b>Emboss</b> Linen Saw Cut Natural Timber	<b>Design</b> Clean Oak San Marcus Oak	<b>Emboss</b> In-Register In-Register
Size	7" x 48" (177.8mm x 1219.2mm)		9" x 60" (228.6mm x 1524mm)	
Construction	Solid Vinyl Tile/LVT w/Attraxion Magnetic Attachment Technology		Solid Vinyl Tile/LVT w/Attraxion Magnetic Attachment Technology	
Use	Commercial & Residential		Commercial & Residential	
Wear Layer	20 mil (0.5mm)		20 mil (0.5mm)	
Edge Detail	Micro-Bevel Edge		Micro-Bevel Edge	
Finish	FX <sup>3</sup> Surface Protectant with Ultra-Fresh		FX <sup>3</sup> Surface Protectant with Ultra-Fresh	
Gauge	0.098" (2.5mm)		0.098" (2.5mm)	
Pieces/Carton	16		10	
Coverage/Piece	2.33 Sq.Ft. (0.22 Sq.M.)		3.75 Sq.Ft. (0.35 Sq.M.)	
Coverage/Carton	37.33 Sq.Ft. (3.47 Sq.M.)		37.5 Sq.Ft. (3.48 Sq.M.)	
Coverage/Pallet	65 Cartons / Pallet (2,426.67 Sq.Ft. / 225.44 Sq.M.)		60 Cartons / Pallet (2,250 Sq.Ft. / 209.03 Sq.M.)	
Coverage/Container	15 Pallets / Container (36,400 Sq.Ft. / 3,381.67 Sq.M.)		16 Pallets / Container (36,000 Sq.Ft. / 3,344.51 Sq.M.)	
Limited Warranty	Commercial: 15 Years / Residential: Limited Lifetime		Commercial: 15 Years / Residential: Limited Lifetime	

<b>PHYSICAL PROPERTIES &amp; PACKAGING – TILE (FLOATING - 2.5MM GAUGE / 0.5MM WEAR LAYER)</b>				
<b>Collections</b>	<b>Design</b> Belgium Weave	<b>Emboss</b> Linen	<b>Design</b> Smooth Concrete	<b>Emboss</b> Rough Concrete
Size	16" x 32" (406.4mm x 812.8mm)		24" x 24" (609.6mm x 609.6mm)	
Construction	Solid Vinyl Tile/LVT w/Attraxion Magnetic Attachment Technology		Solid Vinyl Tile/LVT w/Attraxion Magnetic Attachment Technology	
Use	Commercial & Residential		Commercial & Residential	
Wear Layer	20 mil (0.5mm)		20 mil (0.5mm)	
Edge Detail	Square Edge		Micro-Bevel Edge	
Finish	FX <sup>3</sup> Surface Protectant with Ultra-Fresh		FX <sup>3</sup> Surface Protectant with Ultra-Fresh	
Gauge	0.098" (2.5mm)		0.098" (2.5mm)	
Pieces/Carton	10		9	
Coverage/Piece	3.56 Sq.Ft. (0.33 Sq.M.)		4 Sq.Ft. (0.37 Sq.M.)	
Coverage/Carton	35.56 Sq.Ft. (3.3 Sq.M.)		36 Sq.Ft. (3.34 Sq.M.)	
Coverage/Pallet	56 Cartons / Pallet (1,991.11 Sq.Ft. / 184.98 Sq.M.)		20 Cartons / Pallet (720 Sq.Ft. / 66.89 Sq.M.)	
Coverage/Container	18 Pallets / Container (35,840 Sq.Ft. / 3,329.64 Sq.M.)		50 Pallets / Container (36,000 Sq.Ft. / 3,344.51 Sq.M.)	
Limited Warranty	Commercial: 15 Years / Residential: Limited Lifetime		Commercial: 15 Years / Residential: Limited Lifetime	

**STANDARDS – MANUFACTURING & USAGE (ASTM F1700)**

Standard	Description	Requirements	Results
ASTM F1700	Classification	Refer to Standard	Class III, Type B
ASTM F386	Thickness	Tolerance: ±0.005" vs. Nominal	Passes Requirements
ASTM F410	Wear Layer Thickness	Commercial Classification: ≥0.020" (0.5mm)	Passes Requirements
ASTM F2421/ ASTM F2055	Size & Squareness	Size, Tolerance: ±0.016"/Linear Foot vs. Nominal Squareness: ≤0.010"	Passes Requirements
ASTM F1914	Residual Indentation	Average <8% Maximum - Any Sample ≤10%	Surpasses Requirements
ASTM F137	Flexibility	No cracks/breaks (1"/25.4mm Mandrel)	Surpasses Requirements
ASTM F2199	Dimensional Stability	≤0.020"/Linear Foot	Surpasses Requirements
ASTM F925	Chemical Resistance	No more than "Slight Change"	Surpasses Requirements
ASTM F1514	Resistance to Heat	Average ΔE < 8.0	Surpasses Requirements
ASTM F1515	Resistance to Light	Average ΔE < 8.0	Surpasses Requirements

**STANDARDS – SAFETY & PERFORMANCE**

Standard	Description	Requirements	Results
ASTM E648	Critical Radiant Flux (Radiant Panel)	Class I: ≥ 0.45 W/cm <sup>2</sup>	Passes Requirements <sup>1</sup>
ASTM E662	Smoke Density	Flaming & Non-Flaming ≤ 450	Passes Requirements <sup>2</sup>
CDPH/EHLB Standard Method v1.2	VOCs/TVOCs, Formaldehyde	Refer to Standard	Passes Requirements
REACH SVHC 191	Substances of Very High Concern	Per Substance: ≤0.1% w/w (weight/weight)	Passes Requirements
ASTM F963	Heavy Metals	Refer to Standard	Passes Requirements
ASTM D7823 / CPSC-CH-C1001-09.3	Phthalates	Refer to Consumer Product Safety Improvement Act (CPSIA)	Passes Requirements
ASTM G21	Antifungal Activity	N/A (No Official Requirements)	Top Surface: 0 (No Growth)
ASTM D2047	Coefficient of Friction / Slip Resistance	N/A (No Official Requirements)	≥0.6 (Dry)
ANSI ESD STM97.2	Body Voltage	N/A (No Official Requirements)	Average (Abs): ≤2.0kV
ASTM F970	Static Load	±0.005", 250-Lbs. Load	Passes Requirements
SIM Test	Static Load Limit	Test to Limit (±0.005")	≥800 psi <sup>3</sup>
ASTM D4060	Abrasion Resistance	N/A (No Official Requirements)	Average: ≥20,000 cycles

**STANDARDS – SOUND**

Product + Assembly	ASTM E90	ASTM E492	ASTM E2179	Results (Remarks)
Metroflor LVT with Attraxion Installed with MagneBuild Underlayment Over 6" Concrete Slab with Drop-Ceiling	STC 62	IIC 51	Not Applicable	Passes IBC <sup>4</sup> requirements of STC ≥ 50 and IIC ≥ 50 for multi-story dwellings

**Footnotes**  
 1) ASTM E648 - Critical Radiant Flux (Radiant Panel): Passes Requirements for Class I per International Building Code (IBC) 2018 & NFPA 101 Life Safety Code  
 2) ASTM E662 - Smoke Density: 450 is the limit established by many state, county, and/or local building and/or fire codes, but is not set as a limit for (resilient) flooring products nationwide. Thus, Smoke Density requirements for flooring products may vary from jurisdiction to jurisdiction. Consult your building inspector / fire marshal to learn more  
 3) ASTM F970 - Static Load Limit: Results of ≥800 psi are from laboratory tests that included the use of MagneBuild Underlayment  
 4) IBC = International Building Code

Ultra-Fresh is a registered trademark of Thomson Research Associates, Inc.